



# MEDIUM TRUCK

## S-210

- Highway pattern with excellent high speed performance
- Low noise and strong wear resistance
- Four main continuous straight grooves channel water for superior tractions



Item	Tire Size, Load Range, & Service Description	PR	Ship Weight lbs.	Meas. Rim Width (inches)	Tread Depth 32nds	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Eclipse Code
------	--	----	------------------	--------------------------	-------------------	----------------	---------------	------------------	-----------------	---------------	------------------	--------------

### S-210

86469	7.50R16LT	BLK	G	14	50	6	15	2888	107	3330	105	8.5	31.9	53861
-------	-----------	-----	---	----	----	---	----	------	-----	------	-----	-----	------	-------

## S-207

- Open shoulder all-steel radial
- Wide and deep transversal grooves provide greater driving force
- Deep tread depth for extended mileage
- Reinforced bead construction and durable carcass for excellent retreading rate



Item	Tire Size, Load Range, & Service Description	PR	Ship Weight lbs.	Meas. Rim Width (inches)	Tread Depth 32nds	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Eclipse Code
------	--	----	------------------	--------------------------	-------------------	----------------	---------------	------------------	-----------------	---------------	------------------	--------------

### S-207

86425	295/75R22.5	BLK	G	14	134	8.25	25	5675	120	6175	120	11.3	39.9	16860
86420	11R22.5	BLK	H	16	136	8.25	25	6005	120	6610	120	11	41.4	2525
86423	11R22.5	BLK	G	14	130	8.25	25	5840	105	6175	105	11	41.4	15939
86426	285/75R24.5	BLK	G	14	138	8.25	25	5675	110	6175	110	10.7	41.3	16861
86424	11R24.5	BLK	G	14	145	8.25	25	6005	105	6610	105	11	43.5	15940
86430	11R24.5	BLK	H	16	144	8.25	25	6610	120	7160	120	11	43.5	2526
86297	315/80R22.5	BLK	M	18	157	9	22	7606	120	8267	120	12.3	42.4	54178

## S-206


- Premium 5-rib all-position steel radial
- Specially designed for steer axles and all-position usage
- Buttress groove inserted in the shoulder resists irregular wear



Item	Tire Size, Load Range, & Service Description	PR	Ship Weight lbs.	Meas. Rim Width (inches)	Tread Depth 32nds	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Eclipse Code
------	--	----	------------------	--------------------------	-------------------	----------------	---------------	------------------	-----------------	---------------	------------------	--------------

### S-206

86338	295/80R225	BLK	M	16	130	9	18	6945	123	7826	123	11.7	41.1	45841
86288	315/80R225	BLK	M	18	143	9	19	7606	120	8267	120	12.3	42.4	54183
86287	315/80R225	BLK	L	20		9	19	7386	123	8819	123	12.3	42.3	54184



**HERCULES TIRES**  
RIDE ON OUR STRENGTH.