

PERFORMANCE

H/P 4000

UTQG: 440-A-B
50 series, 440-A-C



- Performance enhanced tread design for cutting-edge traction in all weather conditions
- Raised white lettering
- Looks as good as it performs


Item	Tire Size & Service Description	Meas. Rim Width (inches)	PSI	Max. Load	Overall Diameter	Section Width	Tread Depth (32 ^{nds})	Ship Weight (lbs.)	Eclipse Code
------	---------------------------------	--------------------------	-----	-----------	------------------	---------------	----------------------------------	--------------------	--------------

H/P 4000 black sidewall sizes

02808	P185/60R14	82T	5.5	44	1047	22.80	7.15	11	16.0	21285
02812	P195/60R15	87T	6.0	44	1201	24.30	7.60	11	19.0	21287
02814	P205/60R15	90T	6.0	44	1301	24.73	7.83	11	20	02814
02806	P235/55R16	96T	7.5	44	1565	26.15	9.65	11	25.0	21284
02805	P215/55R16	91T	7.0	44	1356	25.25	8.83	11	22.0	23853

H/P 4000 raised white letter sidewall sizes

02782	P235/60R14	96T	7.0	44	1565	25.06	9.11	11	23.0	21272
02826	P225/70R14	98T	6.5	44	1653	26.27	8.92	11	24.0	21294
02824	P215/70R14	96T	6.5	44	1565	25.76	8.66	11	22.0	21293
02770	P295/50R15	105S	9.5	35	2039	26.80	11.77	11	32.0	21266
02796	P275/60R15	107T	8.0	44	2149	28.06	10.70	11	31.0	21279
02834	P255/70R15	108T	7.5	44	2205	28.95	10.40	11	30.0	21298
02794	P255/60R15	102T	7.5	44	1874	27.01	9.73	11	28.0	21278
02792	P245/60R15	100T	7.0	44	1764	26.55	9.47	11	26.0	21277
02832	P235/70R15	102T	7.0	44	1874	27.90	9.46	11	27.9	21297
02790	P235/60R15	98T	7.0	44	1653	26.11	9.15	11	25.0	21276
02830	P225/70R15	100T	6.5	44	1764	27.37	8.71	11	25.0	21296
02828	P215/70R15	97T	6.5	44	1609	26.71	8.71	11	23.0	21295
02798	P215/65R15	95T	6.5	44	1521	26.00	8.38	11	22.0	21280



HERCULES TIRES
RIDE ON OUR STRENGTH.