

To obtain the remaining tread depth, take three or four measurements on the tire, one on the inner groove, one or two in the center and one in the outer groove and then average the three or four measurements. Locate (below) the tire's original tread depth. Read down and across matching the tire's measured remaining tread depth. Use the percentages shown as a charge and/or credit towards the purchase of a replacement tire.

The numbers to the left (**60/40**) designate the percentage of usable tread worn, to determine customer's charge for a replacement tire. Numbers to the right (**60/40**) designate the percentage of usable tread remaining, used to determine credit due to customer toward the purchase of a replacement tire.

### ORIGINAL TREAD DEPTH (32NDS)

	9/32	10/32	11/32	12/32	13/32	14/32	15/32	16/32	17/32	18/32	19/32	20/32	21/32	22/32	23/32	24/32	25/32	26/32	27/32	28/32
2/32	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0	100/0
3/32	86/14	88/12	89/11	90/10	91/9	92/8	92/8	93/7	93/7	94/6	94/6	94/6	95/5	95/5	95/5	95/5	96/4	96/4	96/4	96/4
4/32	71/29	75/25	78/22	80/20	82/18	83/17	85/15	86/14	87/13	88/12	88/12	89/11	89/11	90/10	90/10	91/9	91/9	92/8	92/8	92/8
5/32	57/43	63/37	67/33	70/30	73/27	75/25	77/23	79/21	80/20	81/19	82/18	83/17	84/16	85/15	86/14	86/14	87/13	88/12	88/12	88/12
6/32	43/57	50/50	56/44	60/40	64/36	67/33	69/31	71/29	73/27	75/25	76/24	78/22	79/21	80/20	81/19	82/18	83/17	83/17	84/16	85/15
7/32	29/71	38/62	44/56	50/50	55/45	58/42	62/38	64/36	67/33	69/31	71/29	72/28	74/26	75/25	76/24	77/23	78/22	79/21	80/20	81/19
8/32	14/86	25/75	33/67	40/60	45/55	50/50	54/46	57/43	60/40	63/37	65/35	67/33	68/32	70/30	71/29	73/27	74/26	75/25	76/24	77/23
9/32	0/100	13/87	22/78	30/70	36/64	42/58	46/54	50/50	53/47	56/44	59/41	61/39	63/37	65/35	67/33	68/32	70/30	71/29	72/28	73/27
10/32		0/100	11/89	20/80	27/73	33/67	38/62	43/57	47/53	50/50	53/47	56/44	58/42	60/40	62/38	64/36	65/35	67/33	68/32	69/31
11/32			0/100	10/90	18/82	25/75	31/69	36/64	40/60	44/56	47/53	50/50	53/47	55/45	57/43	59/41	61/39	62/38	64/36	65/35
12/32				0/100	9/91	17/83	23/77	29/71	33/67	37/63	41/59	44/56	47/53	50/50	52/48	55/45	57/43	58/42	60/40	62/38
13/32					0/100	8/92	15/85	21/79	27/73	31/69	35/65	39/61	42/58	45/55	48/52	50/50	52/48	54/46	56/44	58/42
14/32						0/100	8/92	14/86	20/80	25/75	29/71	33/67	37/63	40/60	43/57	45/55	48/52	50/50	52/48	54/46
15/32							0/100	7/93	13/87	19/81	24/76	28/72	32/68	35/65	38/63	41/59	43/57	46/54	48/52	50/50
16/32								0/100	7/93	12/88	18/82	22/78	26/74	30/70	33/67	36/64	39/61	42/58	44/54	46/54
17/32									0/100	6/94	12/88	17/83	21/79	25/75	29/71	32/68	35/65	38/62	40/60	42/58
18/32										0/100	6/94	11/89	16/84	20/80	24/76	27/73	30/70	33/67	36/64	38/62
19/32											0/100	6/94	11/89	15/85	19/81	23/77	26/74	29/71	32/68	35/65
20/32												0/100	5/95	10/90	14/86	18/82	22/78	25/75	28/72	31/69
21/32													0/100	5/95	10/90	14/86	17/83	21/79	24/76	27/73
22/32														0/100	5/95	9/91	13/87	17/83	20/80	23/77
23/32															0/100	5/95	9/91	12/88	16/84	19/81
24/32																0/100	4/96	8/92	12/88	15/85
25/32																	0/100	4/96	8/92	12/88
26/32																		0/100	4/96	8/92
27/32																			0/100	4/96
28/32																				0/100

REMAINING TREAD DEPTH (32NDS)



VALUES IN PERCENT (0% / 100%)

EXAMPLE OF WHERE TO TAKE MEASUREMENTS.  
DO NOT TAKE MEASUREMENTS STRAIGHT ACROSS IN ONE DIRECTION.